


Pushbutton Units and Indicator Lights

SIRIUS Metallic 3SB3, ○ Round Design, 22 mm

Complete units

Selection and ordering data

	Version	Color of operator	Contacts	Order No.	List Price \$	Weight approx.	Packs
					1 unit	kg	Unit
Pushbutton unit with flat button 	Pushbutton unit with flat button¹⁾	black	1 NO	3SB36 02-0AA11		0.072	1
		black	1 NC	3SB36 03-0AA11			
		red	1 NC	3SB36 03-0AA21			
		yellow	1 NO	3SB36 02-0AA31			
		green	1 NO	3SB36 02-0AA41			
		blue	1 NO	3SB36 02-0AA51			
		white	1 NO	3SB36 02-0AA61			
		black	1 NO + 1 NC	3SB36 01-0AA11		0.081	1
		red	1 NO + 1 NC	3SB36 01-0AA21			
		yellow	1 NO + 1 NC	3SB36 01-0AA31			
		green	1 NO + 1 NC	3SB36 01-0AA41			
		blue	1 NO + 1 NC	3SB36 01-0AA51			
		white	1 NO + 1 NC	3SB36 01-0AA61			
	Pushbutton unit with extended button	black	1 NO	3SB36 02-0BA11		0.072	1
		black	1 NC	3SB36 03-0BA11			
		red	1 NC	3SB36 03-0BA21			
		yellow	1 NO	3SB36 02-0BA31			
		blue	1 NO	3SB36 02-0BA51			
		white	1 NO	3SB36 02-0BA61			
		black	1 NO + 1 NC	3SB36 01-0BA11		0.081	1
		red	1 NO + 1 NC	3SB36 01-0BA21			
		yellow	1 NO + 1 NC	3SB36 01-0BA31			
		green	1 NO + 1 NC	3SB36 01-0BA41			
		blue	1 NO + 1 NC	3SB36 01-0BA51			
		white	1 NO + 1 NC	3SB36 01-0BA61			

1) For assemblies with spring loaded contact blocks add suffix -OCC0.

Pushbutton Units and Indicator Lights

SIRIUS Metallic 3SB3, ○ Round Design, 22 mm

Complete units

Selection and ordering data

Illuminated pushbutton unit
with flat button



Version	Color of operator	Contacts	Order No.	List Price \$ 1 unit	Weight approx. kg	Packs Unit
Illuminated pushbutton units with flat button³⁾						
with integrated LED 24 V AC/DC Momentary ¹⁾²⁾	red	1 NC	3SB36 46-0AA21		0.083	1
	yellow	1 NO	3SB36 45-0AA31			
	green	1 NO	3SB36 45-0AA41			
	blue	1 NO	3SB36 45-0AA51			
	white	1 NO	3SB36 45-0AA61			
	clear	1 NO	3SB36 45-0AA71			
	red	1 NO + 1 NC	3SB36 47-0AA21		0.09	
	yellow	1 NO + 1 NC	3SB36 47-0AA31			
	green	1 NO + 1 NC	3SB36 47-0AA41			
	blue	1 NO + 1 NC	3SB36 47-0AA51			
	white	1 NO + 1 NC	3SB36 47-0AA61			
	clear	1 NO + 1 NC	3SB36 47-0AA71			
with integrated LED 110 V AC Momentary	red	1 NC	3SB36 50-0AA21		0.083	1
	yellow	1 NO	3SB36 57-0AA31			
	green	1 NO	3SB36 57-0AA41			
	blue	1 NO	3SB36 57-0AA51			
	white	1 NO	3SB36 57-0AA61			
	clear	1 NO	3SB36 57-0AA71			
	red	1 NO + 1 NC	3SB36 51-0AA21		0.09	
	yellow	1 NO + 1 NC	3SB36 51-0AA31			
	green	1 NO + 1 NC	3SB36 51-0AA41			
	blue	1 NO + 1 NC	3SB36 51-0AA51			
	white	1 NO + 1 NC	3SB36 51-0AA61			
	clear	1 NO + 1 NC	3SB36 51-0AA71			
with integrated LED 230 V AC Momentary ¹⁾	red	1 NC	3SB36 54-0AA21		0.083	1
	yellow	1 NO	3SB36 53-0AA31			
	green	1 NO	3SB36 53-0AA41			
	blue	1 NO	3SB36 53-0AA51			
	white	1 NO	3SB36 53-0AA61			
	clear	1 NO	3SB36 53-0AA71			
	red	1 NO + 1 NC	3SB36 55-0AA21		0.09	
	yellow	1 NO + 1 NC	3SB36 55-0AA31			
	green	1 NO + 1 NC	3SB36 55-0AA41			
	blue	1 NO + 1 NC	3SB36 55-0AA51			
	white	1 NO + 1 NC	3SB36 55-0AA61			
	clear	1 NO + 1 NC	3SB36 55-0AA71			
with BA 9s lampholder, without lamp, including holder for 3 elements ¹⁾	red	1 NC	3SB36 07-0AA21		0.083	1
	amber	1 NO	3SB36 06-0AA01			
	yellow	1 NO	3SB36 06-0AA31			
	green	1 NO	3SB36 06-0AA41			
	blue	1 NO	3SB36 06-0AA51			
	white	1 NO	3SB36 06-0AA61			
	clear	1 NO	3SB36 06-0AA71		0.09	
	red	1 NO + 1 NC	3SB36 05-0AA21			
	amber	1 NO + 1 NC	3SB36 05-0AA01			
	yellow	1 NO + 1 NC	3SB36 05-0AA31			
	green	1 NO + 1 NC	3SB36 05-0AA41			
	blue	1 NO + 1 NC	3SB36 05-0AA51			
	white	1 NO + 1 NC	3SB36 05-0AA61			
	clear	1 NO + 1 NC	3SB36 05-0AA71			

1) For assemblies with spring loaded contact blocks add suffix -0CC0.




2) For assemblies with solvent-resistant caps, add suffix -0PA0.

3) For all colors except white, inscription by inserting a label is possible.

Pushbuttons and Indicator Lights

SIRIUS Metallic 3SB3, ○ Round Design, 22 mm

Complete units

Version	Color of operator	Contacts for front plate mounting	Order No.	List Price \$ 1 unit	Weight approx. kg	Packs Unit
	red	1 NC 1 NO + 1 NC	3SB36 03-1CA21		0.100	1
			3SB36 01-1CA21		0.107	1
Mushroom push-pull button						
EMERGENCY-STOP control devices according to EN 418 with yellow name plate, Ø 80 mm, labeled. Can also be used with 3TK28 contactor safety relays (see Section 13)						
	red	1 NC 1 NO + 1 NC	→ 3SB36 03-1HR20		0.131	1
			→ 3SB36 01-1HR20		0.137	1
Mushroom pushbutton, Ø 40 mm with positive latching rotate to unlatch Inscription "EMERGENCY STOP"						
EMERGENCY-STOP mushroom pushbutton with rotary unlocking						
	red	1 NC 1 NO + 1 NC	→ 3SB36 03-1TR20		0.131	1
			→ 3SB36 01-1TR20		0.137	1
Mushroom pushbutton, Ø 40 mm with positive latching pull to unlatch Inscription "EMERGENCY STOP"						
EMERGENCY-STOP mushroom pushbutton with pull-to-unlatch mechanism						

→ Positive opening according to IEC 60947-5-1, Appendix K.







1) For assemblies with spring loaded contact blocks add suffix -0CC0.


* This quantity or a multiple thereof can be ordered

Pushbuttons and Indicator Lights

SIRIUS Metallic 3SB3, ○ Round Design, 22 mm

Complete units

	Version	Color of operator	Contacts for front plate mounting	Order No.	List Price \$ 1 unit	Weight approx. kg	Packs Unit
 Non-illuminated selector switch	Selector switch, 2 switch positions switching sequence O-I 50° operating angle, maintained 	black, standard version ¹⁾	1 NO 1 NO + 1 NC	3SB36 02-2KA11 3SB36 01-2KA11	0.095 0.102	1	
		black, heavy duty version	1 NO 1 NO + 1 NC	3SB36 02-2PA11 3SB36 01-2PA11	0.111 0.119	1	
	Selector switch, 3 switch positions switching sequence I-O-II 2 x 50° operating angle, maintained 	black, standard version ¹⁾	1 NO, 1 NO 1 NO + 1 NC, 1 NO + 1 NC	3SB36 10-2DA11 3SB36 08-2DA11	0.105 0.117	1	
		black, heavy duty version	1 NO, 1 NO 1 NO + 1 NC, 1 NO + 1 NC	3SB36 10-2SA11 3SB36 08-2SA11	0.121 0.134	1	
 RONIS key-operated switch	momentary-contact type 	black, standard version ¹⁾	1 NO, 1 NO 1 NO + 1 NC, 1 NO + 1 NC	3SB36 10-2EA11 3SB36 08-2EA11	0.103 0.119	1	
		black, heavy duty version	1 NO, 1 NO 1 NO + 1 NC, 1 NO + 1 NC	3SB36 10-2TA11 3SB36 08-2TA11	0.122 0.135	1	
	Key-operated switch RONIS, flat, 2 switch positions ¹⁾ , key can be removed in any position switching sequence O-I, 50° operating angle, maintained 	SB 30	1 NO 1 NO + 1 NC	3SB36 02-4AD11 3SB36 01-4AD11	0.119 0.124	1	

	Version	Color of lens	Lamp voltage V	Order No.	List Price \$ 1 unit	Weight approx. kg	Packs Unit
 <p>Indicator light</p>	Indicator light with lens with concentric rings ¹⁾ , with integrated LED	red yellow green blue white clear amber	24 V AC/DC	3SB36 44-6BA20 3SB36 44-6BA30 3SB36 44-6BA40 3SB36 44-6BA50 3SB36 44-6BA60 3SB36 44-6BA70 3SB36 44-6BA00		0.080	1
	with integrated LED	red yellow green blue white clear amber	110 V AC	3SB36 48-6BA20 3SB36 48-6BA30 3SB36 48-6BA40 3SB36 48-6BA50 3SB36 48-6BA60 3SB36 48-6BA70 3SB36 48-6BA00		0.081	1
	with integrated LED	red yellow green blue white clear	230 V AC	3SB36 52-6BA20 3SB36 52-6BA30 3SB36 52-6BA40 3SB36 52-6BA50 3SB36 52-6BA60 3SB36 52-6BA70		0.081	1
	with lampholder BA 9s, (without lamp)	red yellow green blue white clear		3SB36 04-6BA20 3SB36 04-6BA30 3SB36 04-6BA40 3SB36 04-6BA50 3SB36 04-6BA60 3SB36 04-6BA70		0.079	1

1) For assemblies with spring loaded contact blocks add suffix -0CC0.

* This quantity or a multiple thereof can be ordered